

## Declaration of performance: No. CPR-NO1/0050

1. Unique identification code of the product-type: **MURMØRTEL KC 50/50**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:  
**UNIVERSAL MUR OG PUSSMØRTEL (GP)**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**For utvendig og innvendig bruk på vegger, tak, søyler og skillevegger**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI AS – Vallsetvegen, 6 – 2120 Sagstua (Norway)** [www.mapei.no](http://www.mapei.no)
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Ikke relevant**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
**Ingen oppgaver for teknisk kontrollorgan.**
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Ikke relevant**
9. Declared performance:


Essential characteristics	Performance	Harmonised technical specification
<b>Brannpåvirkning:</b> <b>Vann absorpsjon:</b> <b>Vanndamppermeabilitet:</b> <b>Heft:</b> <b>Varmeledningsevne (<math>\lambda_{10, dry}</math>):</b> <b>Bestandighet:</b> <b>Farlige bestanddeler:</b>	<b>Class A1</b> <b>W0</b> <b><math>\mu \leq 30</math></b> <b><math>&gt;0.3 \text{ N/mm}^2</math> – FP:B</b> <b>0.82 W/m·K (tab. Snit verdi; P = 50%)</b> <b>NPD</b> <b>Se sikkerhetsdatablad</b>	<b>NS EN 998-1: 2010</b>

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.



This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: **Trond Hagerud – Managing Director**  
(name and function)

**Sagstua, 01/01/2014**  
(place and date of issue)

  
.....  
(signature)

## CE MARKING according to CPR 305/2011 and NS EN 998-1:2010

	 Vallsetvegen 6, 2120 Sagstua (Norway) <a href="http://www.mapei.no">www.mapei.no</a>														
<p style="text-align: center;"><b>14</b> <b>CPR-NO1/0050</b> <b>NS EN 998-1:2010</b> <b>Murmørtel KC 50/50</b></p> <p style="text-align: center;"><i>General purpose rendering and plastering mortar (GP) for external and internal use on walls, ceilings, columns and partitions.</i></p> <table><tr><td>Reaction to fire:</td><td>Class A1</td></tr><tr><td>Water absorption:</td><td>W 0</td></tr><tr><td>Water vapour permeability:</td><td><math>\mu \leq 30</math></td></tr><tr><td>Adhesion:</td><td><math>&gt;0.3 \text{ N/mm}^2</math> – FP:B</td></tr><tr><td>Thermal conductivity (<math>\lambda_{10, \text{dry}}</math>):</td><td>0.82 W/m·K (tab. mean value; P = 50%)</td></tr><tr><td>Durability:</td><td>NPD</td></tr><tr><td>Dangerous substances:</td><td>See SDS</td></tr></table>		Reaction to fire:	Class A1	Water absorption:	W 0	Water vapour permeability:	$\mu \leq 30$	Adhesion:	$>0.3 \text{ N/mm}^2$ – FP:B	Thermal conductivity ( $\lambda_{10, \text{dry}}$ ):	0.82 W/m·K (tab. mean value; P = 50%)	Durability:	NPD	Dangerous substances:	See SDS
Reaction to fire:	Class A1														
Water absorption:	W 0														
Water vapour permeability:	$\mu \leq 30$														
Adhesion:	$>0.3 \text{ N/mm}^2$ – FP:B														
Thermal conductivity ( $\lambda_{10, \text{dry}}$ ):	0.82 W/m·K (tab. mean value; P = 50%)														
Durability:	NPD														
Dangerous substances:	See SDS														