



tesa® Professional Dobbelsidig monteringsstape Speil



Product Information

BNR 55734, 55758, 55733, 55759, 55732, 55760, 65204, 55761

Produktbeskrivelse

tesa® Powerbond Mirror er en rask og enkel måte å henge speil og andre flate gjenstander opp permanent i fuktige områder.

Funksjoner

- Ideell for speil
- Motstandsdyktig mot fuktighet
- Holder speil på maks. 70 x 70 cm med opp til 4 mm tykkelse
- Passer for fuktige rom, så som bad

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|---------|------------------|---------|
| • Bæremateriale | PE-skum | • Total tykkelse | 1150 µm |
| • Klebetype | Akryl | | |

Egenskaper / ytelsesverdier

- | | | | |
|--------------------------------|--|-------------------------------|---|
| • Aldringsbestandighet (UV) | Ja | • Kan brukes om igjen | Nei |
| • Application temperature from | -10 °C | • Kjemikaliebestandig | Nei |
| • Batterier inkl. | Nei | • Krever batterier | Nei |
| • Bruksområde | Hall, Planteskole,
Baderom, Stue,
Soverom, Hjemme,
Kontor | • Temperature resistance max. | 40 °C |
| | | • Temperature resistance min. | 10 °C |
| | | • UV-bestandig | Ja |
| • Bruksområdet | Innendørs | • Vannrett | Nei |
| • Farlig materiale | Nei | • Velegnede overflater | Fliser, De fleste
plasttyper, Glass,
Metall, Stål |
| • Fjernes uten kleberester | Nei | | |
| • Fuktbestandighet | Ja | | |



tesa[®] Professional Dobbelsidig monteringstape Speil

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>