



Declaration of Performance

LE/DoP-No. 610148000

1. Product name Anchor
2. Type of product ETA-12/0256
Batch number : see packaging of the product under the label – first number is the year, next 2 numbers is the week of production
3. Application

Generic Type	Bonded Anchor with Anchor rod of size M8 to M30 or rebar d8 to d32 for use in concrete
For use in	Non-cracked concrete C20/25 to C50/60 acc. To EN 206:2000-12
Material	Zinc-plated or hot dip galvanized steel: Dry internal conditions M8 to M30 Stainless steel (A4) – 1.4401, 1.4404, 1.4571: Internal and external use without particular aggressive conditions M8 to M30 High corrosion resistance steel (HRC) – 1.4529, 1.4565: Internal and external use without particular aggressive conditions M8 to M30 Reinforcing bar Class B and C as EN 1992-1-1 Annex C Ø8 to Ø32
Use category	Installation in dry and wet concrete (all sizes) or flooded holes (only M8 to M16 and rebar Ø8 to Ø16) <ul style="list-style-type: none"> - Overhead installation - Application in non-cracked concrete: M8 to M30, Rebar Ø8 to Ø32 Application in cracked concrete and and seismic C1: M12 to M30, Rebar Ø12 to Ø32
Loading	Static, Quasi-static, seismic C1
Temperature range	-40°C +40°C (max. short term temperature +40°C; max. long term temperature +24°C) -40°C +80°C (max. short term temperature +80°C, max. long term temperature +50°C) -40°C +120°C (max. short term temperature +120°C, max. long term temperature +72°C)

4. Manufacturer Novatech International NV
Industrielaan 5 B
BE-2250 Olen
T. +32 14 85 97 37
F. +32 14 85 97 38
E. info@tec7.com
5. Representative not applicable
6. System of assessment of constancy of performance System 1

