



# tesa® Extra-Strong Double-Sided Adhesive Tape Permanent



## Product Information

BNR 05672, 05681, 05671, 05686, 05670, 05691, 05696, 05690, 05692

## Product Description

tesa® Flooring Tape Extra Strong Hold is a double-sided flooring tape for the reliable fixation of carpets and PVC in indoor and covered outdoor areas.

## Product Features

- Suitable for all carpets and PVC flooring
- Extra-strong double-sided adhesive
- Can also be used with underfloor heating and in damp rooms
- Easy to tear by hand

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                   |                   |        |
|--------------------|-------------------|-------------------|--------|
| • Type of adhesive | tackified acrylic | • Total thickness | 240 µm |
|--------------------|-------------------|-------------------|--------|

## Properties/Performance Values

- |                         |                    |                               |   |
|-------------------------|--------------------|-------------------------------|---|
| • Tensile strength      | 30 N/cm            | • Residue-free removability   | no  |
| • Adhesive strength     | Very high adhesion | • Reusable                    | no  |
| • Applicationfield      | Home               | • Solvent free                | no  |
| • Area of use           | In- and Outdoor    | • Spare part service          | no  |
| • Batteries included    | no                 | • Suitable surfaces           | Tiles, Brick, Most plastics, Glass, Acrylic glass, Cardboard, Plaster, Paper, Metal, Steel, Stone |
| • Batteries required    | no                 |                               |   |
| • Chemical Resistance   | yes                |                               |   |
| • Ecofriendly packaging | no                 |                               |   |
| • Hazard material       | no                 |                               |   |
| • Material              | PP (polypropylene) | • Tear resistance             | yes   |
|                         |                    | • Temperature resistance      | yes   |
|                         |                    | • Temperature resistance max. | °C  |
|                         |                    | • Temperature resistance min. | °C  |
|                         |                    | • Tensibility                 | 20 %  |



# tesa<sup>®</sup> Extra-Strong Double-Sided Adhesive Tape Permanent

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>