

# Leica Geosystems

## L2P5 Technical Data

Range*	82 ft
Range with laser receiver*	262 ft
Pulse power for receiver	yes, auto
Smart targeting	not available
Self-leveling range	± 4°
Self-leveling time	<3 seconds
Out of level warning	yes – blink lines every 5 seconds
Leveling system	automatic pendulum - lockable
Leveling accuracy	±0.002 in/ft = ±0.08 in @ 33ft
# of laser points	4
# of laser lines	2
Beam direction	vertical, horizontal, up, down, right, left
Beam angle	vertical/> 170°, horizontal/> 180°
Laser line width at 16 ft	<0.08 in
Horizontal line accuracy	±0.004 in/ft = ±0.11 in @ 33ft
Vertical line accuracy	±0.004 in/ft = ±0.11 in @ 33ft
Point accuracy	±0.002 in/ft = ±0.08 in @ 33ft
Laser type	635 ± 5nm/Class 2 (IEC 60825-1)
Laser output power	30 mW
Laser visibility	0.2 spectral efficiency
Drop resistance	1.64 ft
Battery type	Li-Ion rechargeable battery pack 5200 mAh/ 18.7 Wh (or AA 3 x 1.5V)

## Leica Geosystems

Operating time (Li-Ion)	44h (1 beam + 2 points) continuous 26h (2beam + 4 points) continuous
Operating time (Alkaline)	13h (1 beam + 2 points) continuous 8h (2 beams + 4 points) continuous
Automatic shut-off	available
Protection class	IP54
Dimensions (L x W x H)	4.33 x 2.36 x 3.93 in
Weight with Li-Ion batteries	1.17 lbs
Operating temperature	+14 to +122° F
Storage temperature	-13 to +158° F
Tripod thread	1/4" (5/8" with adapter)
Scope of delivery	L2P5, TWIST 360, Li-Ion battery pack, charger, Alkaline battery tray, Target plate, Hard case, Calibration certificate

\*depending on lighting conditions