

Nordic XL Pro TECHNICAL DATASHEET

MADE IN BELGIUM



Nordic XL PRO

PRODUCT DESCRIPTION

Dimensions	2038 L x 241 W x 8 TH mm
Packaging	Box: 6 boards - 2,95 m ² (20,7 kg) Pallet: 54 boxes - 159,14 m ² (1159 kg)
Composition	Paper impregnated with melamine resin
> surface layer	Moisture-resistant High Density Fibreboard, HDF
> Substrate	Paper impregnated with melamine resin
> Backing	
Features	Matlook, 4 bevels, X-Long, X-Large
Installation	5G Loc under licence of Välinge Innovation AB
Installation instructions	See box inlay or www.berryalloc.com

REQUIREMENTS

General requirements	According EN13329
Classification requirements	Class 23/32

CHARACTERISTICS

METHOD

TEST RESULTS

Abrasion resistance	EN 13329	AC4 (IP \geq 4.000)
Impact resistance	EN 13329	Small ball \geq 12N - Big ball \geq 750mm
Resistance to staining	EN 438	5 (groups 1 + 2); 4 (group 3)
Resistance to cigarette burns	EN 438	4
Effect of a furniture leg	EN 424	No damage (foot type 0)
Effect of a castor chair	EN 425	No change in appearance or damage
Thickness swelling	EN 13329	\leq 18%

CE - CLASSIFICATION ACCORDING EN14041

Fire resistance	C _f -S1
Formaldehyde	E1
Slipperiness	DS

OTHER TECHNICAL DATA

Labelling according to French VOC emission regulation	A+
Floor heating/cooling	See specific instructions on www.berryalloc.com
Thermal resistance in combination with underlay Excellence Plus	0,08 m ² K/W

WARRANTY AND MAINTENANCE

Residential warranty	20 years
Warranty conditions	See www.berryalloc.com
Care and maintenance	See www.berryalloc.com