

01/2021

	contains	m <sup>2</sup>	ft <sup>2</sup>	weight
1 pack Ocean 8 XL	6 planks	2,95 m <sup>2</sup>	31.72 ft <sup>2</sup>	21,1 kg
1 pallet Ocean 8 XL	54 packs	159,14 m <sup>2</sup>	1712.92 ft <sup>2</sup>	1159 kg



## product specifications

Dimensions	2038 x 241 mm
Total thickness	8 mm
Bevels	4
Loc System	5G Loc under licence of Välinge Innovation AB
Level of use according to European standard EN13329	23 heavy domestic use
	32 general commercial use
Residential warranty	lifetime
Commercial warranty	5 years

Warranty conditions on [www.berryalloc.com](http://www.berryalloc.com)

## composition

Surface layer	Direct laminated paper, impregnated with melamine resin
Substrate	Moisture resistant High Density Fiberboard (HDF) treated with hydro+ water repelling technology
Backing	Direct laminated paper, impregnated with melamine resin

## test results

Abrasion resistance	EN13329	AC4 (IP≥4000)
Impact resistance	EN13329	Small ball : ≥ 12 N - Big ball : ≥ 750 mm
Thickness swelling	EN13329	12% (requirement ≤ 18%)
Fire resistance	EN14041	Cfl-S1
Formaldehyde emission	EN14041	E1
Slip resistance	EN14041	DS
Density	EN323	900 kg/m <sup>3</sup>
Resistance to staining	EN438	5 (groups 1+2) ; 4 (group 3)
Effect of a furniture leg	EN424	No damage (foot type 0)
Effect of a castor chair	EN425	No change in appearance or damage
Thermal resistance in combination with underlay Excellence Plus	ISO 8302	0,08 m <sup>2</sup> K/W – Suitable for floor heating/cooling. Detailed instructions on <a href="http://www.berryalloc.com">www.berryalloc.com</a>

## certificates/labels

- DOP : 170-DPLA18-1
- Sustainability of forests : PEFC certified (07-31-229)
- Labelling according to French VOC emission regulation : A+

