

## DECLARATION OF PERFORMANCE

NO: 0303

**1. Identification code of the product type**

0,75 mm LINEFLEX EPDM MEMBRANE

**2. Type, batch or serial number or other identifying mark to identify the construction product**

Batch N°. as shown on the label and on the product

**3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification**

Flexible sheets for use waterproofing and underlays for discontinuous roofing

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer****LINEFLEX**

AK-İZO Yalıtım Sistemleri San. Ve Tic. A.Ş.

DOSAB, Reyhan Sk., No:3, Osmangazi / BURSA / TÜRKİYE

**5. Name and contact address of the authorised representative**

Not relevant

**6. System for assessment and verification of constancy of performance of the construction Product**

System 3 / The notified body

Centrum Stavebního Inženýrství (CSI) – IN 1390

**7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**

EN 13859-1:2010

Efectis Era Avrasya Test Laboratory / Notified Body Nr: 2184 / Accredited Body Nr: AB – 0330 - T

Reaction to Fire Classification Report No.: ERA – 14 – 131

Centrum Stavebního Inženýrství (CSI) / Notified Body Nr: 1390 / Accredited Body Nr: 1007.6

Determination Of Watertightness Test Report No.: AP492 – 05/08

## 8. Declared Performance

| Basis Characteristics  | Performance | Assessment and Verification of Constancy of Performance | Harmonized technical standards |
|--|-------------|---|--------------------------------|
| Reaction to Fire (EN 13501-1:2007+A1:2009 and EN ISO 11925-2)                                  | Class E     | System 3  | EN 13859-1:2010                |
| Determination of Watertightness (EN 1928:2007)<br>- Before Ageing                              | Class W1    |   |                                |
| <b>Tensile Properties</b>  |             |   |                                |
| Tensile Strength (MD*) (EN 1296 afterwards to EN 12311-1)<br>- Before Ageing<br>- After Ageing | NPD<br>NPD  | System 3  |                                |
| Tensile Strength (CD*) (EN 1296 afterwards to EN 12311-1)<br>- Before Ageing<br>- After Ageing | NPD<br>NPD  |   |                                |
| Elongation at Break (MD*)<br>- Before Ageing<br>- After Ageing                                 | NPD<br>NPD  |   |                                |
| Elongation at Break (CD*)<br>- Before Ageing<br>- After Ageing                                 | NPD<br>NPD  |   |                                |
| Tear Resistance (EN 12310-1:2001)<br>- Before Ageing<br>- After Ageing                         | NPD<br>NPD  | System 3  |                                |
| Determination of foldability at low temperature (EN 495-5)                                     | -40 °C      |   |                                |

**MD\***: Machine Direction

**CD\*/KD\***: Cross Direction

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by;

**Name And Function** : İskender ULUSAY/ CEO

**Place And Date Of Issue** : 26.05.2021

**Signature** :

**Date** : 26.05.2021